



HQLM-3120W 31-inch 4K/HD Multi-format LCD Monitor

HDMI™ 4K HDR



The HQLM-3120W is equipped with 2 channels of 12G-SDI input as standard for efficient configuration with 4K equipment such as cameras and switchers. In addition, this monitor includes 3G-SDI, HD-SDI and HDMI inputs as standard. It has the flexibility to work with various interfaces in the image production field. By employing a 31.1-inch 4096x2160 pixel UHD LCD panel using LED backlight, it can reproduce high resolution 4K and 2K images.

31-inch 4K LCD	4096x2160 pixel	Viewing Angle 178degree(H/V)	Contrast Ratio 1500:1	Brightness 350cd/m²	
ITU-R BT.2020/ACES/DCI-P3	12G-SDI	3G-SDI	HD-SDI	HDMI (HDCP2.2)	Embedded Audio Output
Embedded Audio Meter	Stereo Speaker Out	5.1ch Surround Down-mix			
HDR(HLG)	HDR(PQ)	HD/UHD (2K/4K)	Remote (Parallel)	Remote (Ethernet)	Remote (RS485)
Marker	Test Signal Generator	Mix Test Signal	VITC/LTC Display	WFM Monitoring Display	Mouse Menu Control
Multi-View	Vector Scope Display	UMD/IMD Display	Closed Caption	Payload*2 ID	Auto *3 Calibration
W750xH459xD107mm (W29.52xH18.07xD4.21inches)		14.5kg (31.96 lbs)			

HQLM-1720WR 17-inch 4K/HD Multi-format LCD Monitor

HDMI™ 4K HDR



The HQLM-1720WR is equipped with 2 channels of 12G-SDI input as standard for efficient configuration with 4K equipment such as cameras and switchers. In addition, this monitor includes 3G-SDI, HD-SDI and HDMI inputs as standard. It has the flexibility to work with various interfaces in the image production field. By employing a 16.5-inch 3840x2160 pixel UHD LCD panel using LED backlight, it can reproduce high resolution 4K and 2K images.

17-inch 4K LCD	3840x2160 pixel	Viewing Angle 178degree(H/V)	Contrast Ratio 800:1	Brightness 450cd/m²	
ITU-R BT.2020/ACES/DCI-P3	12G-SDI	3G-SDI	HD-SDI	HDMI (HDCP2.2)	Embedded Audio Output
Embedded Audio Meter	Stereo Speaker Out	5.1ch Surround Down-mix			
HDR(HLG)	HDR(PQ)	HD/UHD (2K/4K)	Remote (Parallel)	Remote (Ethernet)	Remote (RS485)
Marker	Test Signal Generator	Mix Test Signal	VITC/LTC Display	WFM Monitoring Display	Mouse Menu Control
Multi-View	Vector Scope Display	UMD/IMD Display	Closed Caption	Payload*2 ID	Auto *3 Calibration
W428xH309xD145mm (W16.85xH12.17xD5.7inches)		8.5kg (18.74 lbs)			

*1 The American Society of Cinematographers Color Decision List
 *2 12G-SDI : ITU-R BT.2077-2 / 3G-SDI : ITU-R BT.1120-9
 *3 Available from November 2019.