

17.3" Cat5 LCD KVM over IP Switch 1-Local / 1-Remote Access

(HT2708 / HT2716 / HT2724 / HT2732)




Overview

Featuring an integrated LCD monitor, keyboard, and touchpad in a 1U rack-mountable housing, the HT27xx series LCD KVM over IP Switch is a control unit that allows secure access to 8/16/24/32 computers from a single KVM console.


The HT27xx series features IP-based connectivity that allows local and remote operators to monitor and access the computers. With TCP/IP communications protocol, the HT27xx series can be accessed from any computer on the LAN, WAN or Internet.


It's easy to set up the HT27xx series, just plug the cable into the appropriate port, no software needed, no complicated installation procedures, and no compatibility issues. Connect computers with compact RJ-45 connectors and Cat 5e/6 cable, transmitting distance is up to 100m.



1 LCD Monitor	6 Touchpad
2 Rear Bracket Slot	7 Handle
3 Display Menu Buttons	8 Release Switch
4 Mounting Bracket	9 Display Panel
5 Keyboard	10 Port Selection Buttons

Structure





1	Ground Connection Screw	5	USB Port
2	Power input(AC or DC)	6	RS485 Port
3	Power switch	7	Console Monitor Port
4	LAN port	8	Host Port

Features

Hardware Features

- 17.3" FHD TFT LCD monitor with highlight, high definition and high resolution
- Rack-mountable in 1U system rack
- Full size keyboard with integrated number pad
- Integrated trackball – eliminates the need for a separate, external mouse
- Dual power supply

Local Console

- Control up to 8 / 16 / 24 / 32 computers
- Support 1 local user and 1 remote user, port share mode allows local and remote users to gain access to a server simultaneously
- Easy-to-use switching by browser-based UI interface, hotkeys and pushbuttons
- Support servers with VGA/DVI/HDMI/DP port
- Multiplatform client support (Windows, Linux, Unix, Mac, Solaris (Sun), Redhat, Ubuntu)
- Local Console, Browser, and AP GUIs offer a unified Multilanguage interface
- Local resolution is up to 1280x1024@60Hz
- Support mouse synchronization mode – automatically synchronizes the local and remote mouse movements
- Video synchronization with local console – EDID information for local console display can be stored in the host module for video resolution optimization
- Keyboard and mouse emulation to ensure the normal booting
- Auto scan feature for monitoring user-selected computer
- Hot pluggable – add or remove computers without having to power down the switch


Remote Console

- Adaptive 10 / 100 / 1000 Mbps network
- WEB browser-based remote management
- A Windows client is available for remote access
- BIOS-level access
- Video quality and video tolerance can be adjusted to optimize data transfer speed, data transfer speed is up to 30

FPS

- Full screen or scalable video display
- Remote resolution is up to 1920x1080@60Hz
- Remote users and local users can control the same server/computer synchronously
- Support AES / DES / 3DES encryption
- Support audit function – allows the administrator to audit the device through the system log and operation log
- Exit Macros support
- Configurable user and group permissions for server access and control
- Message Board for communication among remote users
- Support firmware upgrade

Connection Diagram



Package Contents

- 1x KVM over IP console
- 8/16/24/32x USB KVM Dongle - KCM-1200U
- 2x Mounting Rails
- 1x Shield Network Cable
- 1x Power Cord
- 1x Ground Wire
- 1x Quick Start Guide
- 1x User Manual

Specifications

Model		HT2708	HT2716	HT2724	HT2732
Computer Connections	Direct	8	16	24	32
	Max	8	16	24	32
Port Selection	Keyboard, Mouse	Button, UI, Web			
LCD Monitor	Model	FHD TFT			
	View Area	17.3"			
	Optimum Resolution	1920x1080@60Hz			
	Color	16.7 M			
	Brightness	400cd/m ² (T y p)			
	Contrast Ratio	600: 1 (T y p)			
	Pixel Pitch(mm)	0.1989(H) x 0.1989(W)			
Mouse	X/Y Resolution	>1000 points / inch, (40 points/mm)			
	Scroll Wheel	Supports Scroll Wheel function			
Keyboard	99 keys (82 keyboard + 17 number pad)				
Remote	Remote Control	KVM Control (ActiveX)			
	Management	Web			
	Security	DES Encrypted			
	Resolution	1920x1080@60Hz			
Power Input	100V- 240Vac, 50-60Hz, <1.5A				
Power Consumption	23W	25W	28W	28W	
Operating Temperature	0 — 50 °C				
Store Temperature	-20 —60 °C				
Humidity	0~80% RH, non-condensing				
Net Weight	11.5kg	11.5kg	12kg	12kg	
Product Dimension (W x D x H)	448mmx525.6mm mmx42.5mm				
Package Dimension (W x D x H)	765mmx615mmx185mm				