

# Specifications

## NAV 10SD 501

**TRUE 4K specification**

Max. 4K Capabilities		
Resolution and Refresh Rate	Chroma Sampling	Max. Bit Depth per Color
4096 x 2160 at 60 Hz <sup>1</sup>	4:4:4	8 bit
3840 x 2160 at 60 Hz		
4096 x 2160 at 30 Hz		
3840 x 2160 at 30 Hz	4:2:0	10 bit
4096 x 2160 at 60 Hz		
3840 x 2160 at 60 Hz		

Frame rate<sup>2</sup> ..... 24, 25, 30, 50, or 60 fps

Chroma sampling<sup>2</sup> ..... 4:4:4, 4:2:2, or 4:2:0

Color bit depth<sup>2</sup> ..... 8, or 10 bits per color

Signal type ..... DVI v 1.0, HDMI v1.4 and v2.0, HDCP v1.4 and v2.3

Max. video data rate ..... 18 Gbps (6 Gbps per color)

**NOTE:** <sup>1</sup>4096 x 2160 @ 50-60 Hz is available only for HDMI connectors.

**NOTE:** <sup>2</sup>Subject to the maximum data rate limit. Use our calculator at [www.extron.com/8Kdatarate](http://www.extron.com/8Kdatarate) to determine video parameters supported by this data rate.

### Video input stream

Number/signal type ..... 1 PURE3® digital video over IP

Connector ..... 1 SFP+ connector (SM or MM)

### Video processing

Digital sampling ..... 8 or 10 bits per color; 600 MHz pixel clock maximum

Compression ..... PURE3

Latency ..... <1 frame (encode/decode)

**NOTE:** Indicates minimum end-to-end latency. Network and video processing dependencies may apply.

Scaling ..... Vector™

### Video output

**NOTE:** Appropriate DVI-D to HDMI or DisplayPort to HDMI cables or adapters are required for DVI or DisplayPort signal output.

Number/signal type ..... 1 digital HDMI video

Connectors ..... 1 female HDMI type A

Resolution range ..... Up to 4K (4096x2160 at 60 Hz) and UHD (3840x2160 at 60 Hz)

## Specifications • NAV 10SD 501 (Continued)

Scaled resolution ..... 640x480<sup>8</sup>, 800x600<sup>8</sup>, 1024x768<sup>8</sup>, 1280x768<sup>8</sup>, 1280x800<sup>8</sup>, 1280x1024<sup>8</sup>, 1360x768<sup>8</sup>, 1366x768<sup>8</sup>, 1400x1050<sup>8</sup>, 1440x900<sup>8</sup>, 1600x900<sup>8</sup>, 1600x1200<sup>8</sup>, 1680x1050<sup>8</sup>, 1920x1200<sup>8</sup>, 2048x1200<sup>8</sup>, 2048x1536<sup>8</sup>, 2056x1080<sup>8</sup>, 2560x1080<sup>8</sup>, 2560x1440<sup>8</sup>, 2560x1600<sup>8</sup>, bypass\*, 480p<sup>7,8</sup>, 576p<sup>6</sup>, 720p<sup>3,4,5,6,7,8</sup>, 1080p<sup>1,2,3,4,5,6,7,8</sup>, 2048x1080 (2K)<sup>1,2,3,4,5,6,7,8</sup>, 3840x2160<sup>1,2,3,4,5,6,7,8</sup>, 4096x2160<sup>1,2,3,4,5,6,7,8</sup>  
<sup>1</sup> = 23.98 Hz, <sup>2</sup> = 24 Hz, <sup>3</sup> = 25 Hz, <sup>4</sup> = 29.97 Hz, <sup>5</sup> = 30 Hz, <sup>6</sup> = 50 Hz, <sup>7</sup> = 59.94 Hz, <sup>8</sup> = 60 Hz

**NOTE:** When the output resolution is set to "bypass," the input signal is output without scaling.

Standards ..... DVI v1.0, HDMI v1.4 and v2.0, HDCP v1.4/v2.3

Formats ..... RGB and YCbCr digital video

### Audio

Gain ..... Analog to analog: -6.5dBu balanced, -12.5 dBu unbalanced  
HDMI to analog: -5.3 dBu balanced, -11.3 dBu unbalanced

Frequency response ..... 20 Hz to 20 kHz, ±0.5 dB

THD + Noise ..... <0.1% @ 20 Hz to 20 kHz at nominal level

S/N ..... Analog to digital: >90 dB, at full scale output, unweighted  
Digital to analog: >90 dB, at maximum balanced output, unweighted  
Analog to analog: >90 dB, at maximum balanced output, unweighted

Crosstalk ..... ≤-80 dB @ 1 kHz, fully loaded

Stereo channel separation ..... >80 dB @ 1 kHz

Sampling rates ..... 48 kHz

Bit depths ..... 24 bit

### Audio input stream

Number/signal type ..... 1 audio over IP LPCM or AES67

Connector ..... 1 SFP+ connector (SM or MM)

### Audio output

Number/signal type ..... 1 analog stereo, unbalanced or balanced  
1 digital stereo, de-embedded from HDMI

Connectors ..... (1) 3.5 mm captive screw connector, 5 pole  
1 female HDMI (shared with video output)

Supported formats ..... LPCM (2 channel), analog stereo

Impedance ..... 50 ohms unbalanced, 100 ohms balanced

Maximum level (Hi-Z) ..... >+15 dBu balanced, +9 dBu unbalanced

Gain error ..... ±0.5 dB channel to channel

Gain range ..... Adjustable, -18 dB to +24 dB

Volume control range ..... -100 dB to 0 dB (control 0 to 100 in 1 dB steps)

**NOTE:** 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV ≈ 2 dBu

### Network interconnection (NAV)

Number/signal type ..... 2 fiber optic

Connectors ..... (1) 10G SFP+ connector, 2 LC connectors

Termination ..... MDI (SFP+)

Ethernet standards ..... 10 Gb Ethernet (802.3ae), 10GBase-LR (SFP+) SM, and 10GBase-SR (SFP+) MM

Protocols

Streaming ..... SRTP (AES-128) on video, audio, and USB

Transport ..... Multicast UDP

All supported ..... DHCP, HTTPS, IGMPv2/v3, IPv4, PTPv2, QoS, SSH, TCP, UDP

Security ..... AES-256, 802.1X, Active Directory authentication

## Specifications • NAV 10SD 501 (Continued)

Signal transmission distance

Singlemode .....	10 km (6.25 miles) with singlemode (SM) cables with 10GBASE-LR (SFP+)
Multimode .....	400 m (1312') with 50/125 µm OM4 cables with 10GBase-SR (SFP+)

**NOTE:** Operating distance is approximate. These are typical maximum distances that may vary depending on factors such as fiber type, fiber bandwidth, connector splicing, losses, modal or chromatic dispersion, environmental factors, and kinks.

Nominal peak wavelength ..... 850 nm for multimode, 1310 nm for singlemode

Transmission power

Singlemode .....	-5.2 dBm, minimum
Multimode .....	-3.3 dBm, minimum

Maximum receiver sensitivity

Singlemode .....	-12.6 dBm, maximum
Multimode .....	-13.0 dBm, maximum

Optical loss budget

Singlemode .....	7.4 dB, maximum
Multimode .....	9.7 dB, maximum

### Network extension (EXT)

Connector..... 1 RJ-45 female

Termination ..... Auto-MDIX, TIA/EIA T568B

Ethernet standards ..... 1 GbE (802.3ab), 10/100/1000 Base-T, half/full duplex with auto-detect

Signal transmission distance..... 330' (100 m) using CAT-5e/6/6a/7 cables

### USB extension (USB)

USB device port — Host mode configuration

Number/signal type .....	1 USB 2.0 high speed
Connector .....	1 USB type C female
Power.....	N/A
Maximum built-in USB hubs ....	1
Minimum built-in USB hubs ....	0
Optional built-in USB hubs .....	1 (peripheral emulation enabled)

USB device port configuration — Device mode configuration (default)

Number/signal type .....	1 USB 2.0 high speed
Connector .....	1 USB type C female
Power.....	5V DC, 500mA (when in device mode)
Maximum built-in USB hubs ....	0
Minimum built-in USB hubs ....	0
Optional built-in USB hubs .....	0

Host support..... xHCI (USB 3.0), EHCI (USB 2.0), OHCI/UHCI (USB 1.1)

Data rates ..... Low speed (1.5 Mbps), full speed (12 Mbps), high speed (480 Mbps)

Traffic types..... Bulk, control, interrupt, and isochronous

Network switch hops ..... 5 hops (typical)

**NOTE:** Network switch hop limitations may apply. Typical limit is up to five network switches.

# Specifications • NAV 10SD 501 (Continued)

## Communications - external devices

Serial	
Quantity/type.....	1 bidirectional RS-232
Connector .....	(1) 3.5 mm captive screw connector, 5 pole (shared with IR port)
Baud rate and protocol.....	300 to 115200 baud (9600 baud = default) 8 (default) or 7 data bits 1 (default) or 2 stop bits no parity (default), even or odd parity
Pin configuration.....	Tx, Rx, and Gnd
IR control	
Quantity/type.....	1 TTL level (0 to 5 V) infrared (carrier and non-carrier) up to 300 kHz
Connector .....	(1) 3.5 mm captive screw connector, 5 pole (shared with RS-232)
Pin configuration.....	S = signal and G = Gnd
IR output carrier frequency .....	30 kHz to 300 kHz
CEC control .....	1 HDMI type A connector
USB configuration port	
Quantity/type.....	1 front panel USB mini-B
Standard .....	Ethernet over USB

## General

Power supply.....	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 2.0 A, 24 watts
Power consumption	
Device .....	TBD watts
Device and power supply .....	TBD watts
Temperature/humidity .....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +104 °F (0 to +40 °C) / 10% to 85%, noncondensing
Cooling .....	Fan, air flows from top to rear
Thermal dissipation	
Device .....	71.7 BTU/hr
Device and power supply .....	81.9 BTU/hr
Mounting	
Rack mount.....	Yes, with optional rack shelf
Furniture mount.....	Yes, with optional under desk mounting kit
Enclosure type .....	Metal
Enclosure.....	1.00" H x 8.75" W x 6.00" D (half rack wide) (25 mm H x 222 mm W x 152 mm D)
Product weight .....	1.5 lbs (0.68 kg)
Regulatory compliance.....	CE, c-UL UL,C-tick, FCC Class A, ICES, VCCI, Complies with the appropriate requirements of RoHS, WEEE
Product warranty .....	3 years parts and labor
Everlast power supply warranty.....	7 years parts and labor

**NOTE:** All nominal levels are at ±10%.

**NOTE:** Specifications are subject to change without notice.

**NOTE:** Shipping weights and dimensions are available at [www.extron.com](http://www.extron.com).