

LiveShell W

CDP-LS05A



LiveShell W supports switching between two screens, the top model in the series is now available

The latest model of Cerevo's live distribution equipment "LiveShell series", which is used in more than 85 areas around the world, **live shell w**, LiveShell W.

2-input video switching and video effect functions are condensed into a compact housing. It has a wide variety of input/output terminals such as monitor output and audio input. In addition, video switching can be performed using the control dial and video select button on the main unit.

● Product specifications ●

Video maximum resolution	1920 x 1080 60fps (up to 3 simultaneous streams) *Up to 2 when using the recording function
---------------------------------	---

Video encoding method	H.264
Audio coding method	AAC-LC
video bitrate	128kbps to 20Mbps
Audio sampling rate/bit depth/bit rate	48kHz/16bit/48kbps to 256kbps
Supported delivery protocols	RTMP/RTMPS client, RTSP server, MPEG2-TS over UDP
recording media	microSD card (SDHC/SDXC standard), USB memory (both formatted with FAT32 or exFAT)
recording stream	Encoder stream identical to delivery output
video input	HDMI 2 system * HDCP is not supported
Video input resolution	HDMI (1080p/60(59.94), 1080p/50, 1080p/30(29.97), 1080p/25, 1080p/24(23.976), 1080i/60(59.94), 1080i/50, 720p/60(59.94), 720p /50, 720p/30(29.97), 720p/25, 720p/24(23.976), 576p/50, 480p/59.94, VGA)
Voice input	Digital audio: 2 HDMI lines *Common with video input 1 USB line Analog audio: LINE-IN (stereo), MIC-IN (monaural)
Video monitor output	HDMI
Audio monitor output	HDMI Audio
Video switching effect	Cut, Mix, Wipe

video compositing effect	Picture-in-picture, chroma key, split screen (center split/seminar mode)
telop synthesis	Text placement, transparent PNG image synthesis
Operation UI	LiveShell Studio (WebApp)/main unit operation (main unit button)
Internet connection	Wired LAN (10BASE-T/100BASE-TX/1000BASE-T) Wireless LAN (IEEE 802.11a/b/g/n/ac) LTE (*An optional LTE modem is required) *Wireless LAN and LTE are used exclusively will be
Supported network protocol	IPv4/IPv6
power supply	Power can be supplied from a 5V/3A (USB Type-C x 2) AC adapter or an external mobile battery (sold separately).
body size	W: 145 mm × D: 100 mm × H: 42 mm
mass	500g (LiveShell W body only)
Included items: LiveShell W	Main unit x 1, dedicated carry case x 1, LiveShell W quick setup guide x 1, wireless LAN adapter x 1, AC adapter (Anker PowerPort III Nano 20W) x 1, power supply USB cable x 1 may vary.
Bundled items: Accessories sold separately	Main unit x 1, dedicated carrying case x 1, LiveShell W quick setup guide x 1
Optional accessories	Purchase a wireless LAN adapter and AC adapter (USB cable included for power supply) as needed.